

SC 810

Recommended Application:

Highway

Optional Application:

Regional

Trailer Axle

Medium and Long Distances



CHARACTERISTICS

Tread with side wings and rounded shoulders to minimize the effect of side drag in maneuvering.

TECHNICAL DATA

| N# | Width | | Tread Depth | | Weight/m/Lbs./Foot | | | Weight/unit/Lbs. | | Recommended Tire | Size | Length | |
|-----|-------|-------|-------------|-------|--------------------|-------|--------|------------------|-------|----------------------------------|------|--------|--------|
| | mm | In | mm | In | kg/m | Lbs/m | Lbs/ft | kg | Lbs | | | mm | ft |
| 7.5 | 200 | 7 7/8 | 9 | 11/32 | 2,18 | 4,83 | 1,47 | 6,75 | 14,88 | 9.00R20 | P | 3,085 | 10,121 |
| 7.5 | 200 | 7 7/8 | 9 | 11/32 | 2,18 | 4,83 | 1,47 | 7,05 | 15,54 | 10.00R20 11R22.5 | M | 3,212 | 10,538 |
| 7.5 | 200 | 7 7/8 | 9 | 11/32 | 2,18 | 4,83 | 1,47 | 7,20 | 15,87 | 11.00R20 11R24.5 | E | 3,289 | 10,791 |
| 8 | 210 | 8 2/8 | 9 | 11/32 | 2,30 | 5,08 | 1,61 | 7,15 | 15,76 | 9.00R20 | P | 3,103 | 10,180 |
| 8 | 210 | 8 2/8 | 9 | 11/32 | 2,30 | 5,08 | 1,61 | 7,40 | 16,31 | 10.00R20 11R22.5 | M | 3,211 | 10,535 |
| 8 | 210 | 8 2/8 | 9 | 11/32 | 2,30 | 5,08 | 1,61 | 7,60 | 16,76 | 12R22.5 11R24.5 | E | 3,292 | 10,801 |
| 8.5 | 215 | 8 5/8 | 9 | 11/32 | 2,40 | 5,30 | 1,61 | 7,50 | 16,53 | 275/80R22.5 | P | 3,123 | 10,246 |
| 8.5 | 215 | 8 5/8 | 9 | 11/32 | 2,40 | 5,30 | 1,61 | 7,70 | 16,98 | 295/80R22.5 | M | 3,205 | 10,515 |
| 8.5 | 215 | 8 5/8 | 9 | 11/32 | 2,40 | 5,30 | 1,61 | 7,90 | 17,42 | 12R22.5 315/80R22.5 11R24.5 | E | 3,288 | 10,787 |
| 8.5 | 220 | 8 5/8 | 9 | 11/32 | 2,44 | 5,39 | 1,64 | 7,65 | 16,87 | 275/80R22.5 | P | 3,134 | 10,282 |
| 8.5 | 220 | 8 5/8 | 9 | 11/32 | 2,44 | 5,39 | 1,64 | 7,80 | 17,20 | 295/80R22.5 | M | 3,190 | 10,466 |
| 8.5 | 220 | 8 5/8 | 9 | 11/32 | 2,44 | 5,39 | 1,64 | 8,10 | 17,86 | 12R22.5 315/80R22.5 11R24.5 | E | 3,302 | 10,833 |
| 9 | 230 | 9 | 9 | 11/32 | 2,57 | 5,67 | 1,73 | 7,95 | 17,53 | 275/80R22.5 | P | 3,088 | 10,131 |
| 9 | 230 | 9 | 9 | 11/32 | 2,57 | 5,67 | 1,73 | 8,25 | 18,19 | 295/80R22.5 | M | 3,206 | 10,518 |
| 9 | 230 | 9 | 9 | 11/32 | 2,57 | 5,67 | 1,73 | 8,45 | 18,63 | 12R22.5 315/80R22.5 11R24.5 | E | 3,294 | 10,807 |

PRECURED TREADS - SILVERCAP



WWW.SILVERCAPRUBBER.COM