

SC 811

Recommended Application:

Highway

Optional Application:

Regional

Trailer Axle

Medium and Long Distances



CHARACTERISTICS

Tread with rounded shoulders to minimize the effect of lateral drag in maneuvers.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8.5	220	8 5/8	12	15/32	2,94	6,48	1,97	9,22	20,33	275/80R22.5	P	3,140	10,301
8.5	220	8 5/8	12	15/32	2,94	6,48	1,98	9,50	20,94	295/80R22.5 11R22.5	M	3,230	10,596
8.5	220	8 5/8	12	15/32	2,94	6,48	1,97	9,68	21,34	11.00R20 11R24.5	E	3,300	10,826
9	230	9	12	15/32	3,07	6,77	2,06	9,63	21,23	275/80R22.5	P	3,140	10,301
9	230	9	12	15/32	3,07	6,77	2,07	9,93	21,89	295/80R22.5 11R22.5	M	3,230	10,596
9	230	9	12	15/32	3,07	6,77	2,06	10,12	22,31	12R22.5 11R24.5	E	3,300	10,826
9.5	240	9 4/8	12	15/32	3,21	7,08	2,29	10,70	23,59	275/80R22.5	P	3,140	10,301
9.5	240	9 4/8	12	15/32	3,21	7,08	2,16	10,38	22,88	295/80R22.5	M	3,230	10,596
9.5	240	9 4/8	12	15/32	3,21	7,08	2,15	10,58	23,32	12R22.5 315/80R22.5 11R24.5	E	3,300	10,826
10	250	9 7/8	12	15/32	3,34	7,36	2,25	10,80	23,81	295/80R22.5	M	3,230	10,596
10	250	9 7/8	12	15/32	3,34	7,36	2,24	11,01	24,27	315/80R22.5	E	3,300	10,826
10.5	260	10 2/8	12	15/32	3,47	7,65	2,33	11,22	24,74	295/80R22.5	M	3,230	10,596

PRECURED TREADS - SILVERCAP



WWW.SILVERCAPRUBBER.COM