

# SC 811W

Recommended Application:

Highway

Optional Application:

Regional

Trailer Axle

Medium and Long Distances



## CHARACTERISTICS

Tread with side wings and rounded shoulders to minimize the effect of side drag in maneuvering.

## TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
7.5	200	7 7/8	12	15/32	2,90	6,39	1,94	9,02	19,89	9.00R20	P	3,120	10,236
7.5	200	7 7/8	12	15/32	2,90	6,39	1,94	9,26	20,41	10.00R20	M	3,200	10,498
8.5	220	8 5/8	12	15/32	3,11	6,86	2,09	9,70	21,38	275/80R22.5	P	3,120	10,236
8.5	220	8 5/8	12	15/32	3,11	6,86	2,09	9,96	21,96	295/80R22.5   11R22.5	M	3,200	10,498
8.5	220	8 5/8	12	15/32	3,11	6,86	2,09	10,22	22,53	11.00R20   11R24.5	E	3,290	10,793
9	230	9	12	15/32	3,30	7,28	2,22	10,29	22,69	275/80R22.5	P	3,120	10,236
9	230	9	12	15/32	3,30	7,28	2,22	10,57	23,30	295/80R22.5   11R22.5	M	3,200	10,498
9	230	9	12	15/32	3,30	7,28	2,22	10,86	23,94	12R22.5   11R24.5	E	3,290	10,793
9.5	240	9 4/8	12	15/32	3,44	7,58	2,31	11,00	24,25	295/80R22.5	M	3,200	10,498
9.5	240	9 4/8	12	15/32	3,44	7,58	2,31	11,32	24,96	12R22.5   315/80R22.5 11R24.5	E	3,290	10,793
10	250	9 7/8	12	15/32	3,62	7,98	2,43	11,59	25,55	295/80R22.5	M	3,200	10,498
10	250	9 7/8	12	15/32	3,62	7,98	2,43	11,94	26,32	315/80R22.5	E	3,300	10,826
10.5	260	10 2/8	12	15/32	3,77	8,31	2,53	12,05	26,57	295/80R22.5	M	3,200	10,498

PRECURED TREADS - SILVERCAP



WWW.SILVERCAPRUBBER.COM