

SC 812

Recommended Application:
Highway
Optional Application:
Regional

Trailer Axle
Medium and Long Distances



CHARACTERISTICS

High performance tread with rounded shoulders to minimize the effect of lateral drag in maneuvering.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/Meter/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8	210	8 2/8	15	19/32	3,35	7,39	2,25	10,51	23,17	9.00R20	P	3,140	10,301
8.5	220	8 5/8	15	19/32	3,51	7,74	2,36	11,01	24,27	275/80R22.5	P	3,140	10,301
8.5	220	8 5/8	15	19/32	3,51	7,74	2,36	11,34	25,00	295/80R22.5 11R22.5	M	3,230	10,596
8.5	220	8 5/8	15	19/32	3,51	7,74	2,36	11,56	25,49	11.00R20 11R24.5	E	3,290	10,793
9	230	9	15	19/32	3,67	8,09	2,46	11,51	25,38	275/80R22.5	P	3,140	10,301
9	230	9	15	19/32	3,67	8,09	2,47	11,86	26,15	295/80R22.5 11R22.5	M	3,230	10,596
9	230	9	15	19/32	3,67	8,09	2,47	12,09	26,65	12R22.5 11R24.5	E	3,290	10,793
9.5	240	9 4/8	15	19/32	3,83	8,44	2,57	12,01	26,48	275/80R22.5	P	3,140	10,301
9.5	240	9 4/8	15	19/32	3,83	8,44	2,58	12,38	27,29	295/80R22.5	M	3,230	10,596
9.5	240	9 4/8	15	19/32	3,83	8,44	2,58	12,62	27,82	12R22.5 315/80R22.5 11R24.5	E	3,290	10,793
10	250	9 7/8	15	19/32	3,99	8,80	2,68	12,90	28,44	295/80R22.5	M	3,230	10,596
10	250	9 7/8	15	19/32	3,99	8,80	2,68	13,14	28,97	315/80R22.5	E	3,290	10,793
10.5	260	10 2/8	15	19/32	4,15	9,15	2,79	13,41	29,56	295/80R22.5	M	3,230	10,596
10.5	260	10 2/8	15	19/32	4,15	9,15	2,79	13,67	30,14	315/80R22.5	E	3,290	10,793

PRECURED TREADS - SILVERCAP



WWW.SILVERCAPRUBBER.COM