

SC 820

Recommended Application:

Highway

Optional Application:

Regional

Drive and Trailer Axles
Short and Medium Distances



CHARACTERISTICS

Traditional tread, high mileage, designed to provide excellent driving performance in regional use.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs/Ft			Weight/unit/Lbs		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8	210	8 2/8	14	18/32	3,18	7,01	2,14	9,93	21,89	9.00R20	P	3,120	10,236
8	210	8 2/8	14	18/32	3,18	7,01	2,14	10,14	22,35	10.00R20 11R22.5	M	3,190	10,465
8.5	220	8 5/8	14	18/32	3,25	7,17	2,19	10,18	22,44	275/80R22.5	P	3,130	10,268
8.5	220	8 5/8	14	18/32	3,25	7,17	2,18	10,42	22,97	295/80R22.5 11R22.5	M	3,210	10,531
9	230	9	14	18/32	3,42	7,54	2,30	10,64	23,46	275/80R22.5	P	3,110	10,203
9	230	9	14	18/32	3,41	7,52	2,29	10,90	24,03	295/80R22.5 11R22.5	M	3,200	10,498
9	230	9	14	18/32	3,38	7,45	2,27	11,22	24,74	12R22.5 11R24.5	E	3,320	10,892
9.5	240	9 4/8	14	18/32	3,54	7,80	2,38	11,04	24,34	275/80R22.5	P	3,120	10,236
9.5	240	9 4/8	14	18/32	3,54	7,80	2,38	11,32	24,96	295/80R22.5	M	3,200	10,498
9.5	240	9 4/8	14	18/32	3,52	7,76	2,36	11,67	25,73	12R22.5 315/80R22.5 11R24.5	E	3,320	10,892
10	250	9 7/8	14	18/32	3,69	8,14	2,48	11,92	26,28	295/80R22.5	M	3,230	10,596
10	250	9 7/8	14	18/32	3,67	8,09	2,47	12,16	26,81	315/80R22.5	E	3,310	10,859
10.5	260	10 2/8	14	18/32	3,84	8,47	2,58	12,30	27,12	295/80R22.5	M	3,200	10,498
10.5	260	10 2/8	14	18/32	3,82	8,42	2,57	12,64	27,87	315/80R22.5	E	3,310	10,859

PRECURED TREADS - SILVERCAP



WWW.SILVERCAPRUBBER.COM