

# SC 860

Recommended Application:

Highway

Optional Application:

Regional

Drive Axle

Medium and Long Distances



## CHARACTERISTICS

Tread with excellent traction power, open shoulders for better water drainage.

## TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
8.5	220	8 5/8	20	25/32	4,15	9,15	2,79	12,81	28,24	275/80R22.5	P	3,090	10,137
8.5	220	8 5/8	20	25/32	4,15	9,15	2,79	13,23	29,17	295/80R22.5   11R22.5	M	3,190	10,465
9	230	9	20	25/32	4,59	10,12	3,07	14,60	32,19	295/80R22.5   11R22.5	M	3,180	10,492
9	230	9	20	25/32	4,59	10,12	3,08	15,09	33,27	12R22.5   11R24.5	E	3,290	10,793
9.5	240	9 4/8	20	25/32	4,79	10,56	3,24	15,34	33,82	295/80R22.5	M	3,180	10,432
9.5	240	9 4/8	20	25/32	4,79	10,56	3,22	15,78	34,79	12R22.5   315/80R22.5 11R24.5	E	3,290	10,793
10	250	9 7/8	20	25/32	4,99	11,00	3,35	15,85	34,94	295/80R22.5	M	3,180	10,432
10	250	9 7/8	20	25/32	4,99	11,00	3,36	16,43	36,22	315/80R22.5	E	3,290	10,793
10.5	260	10 2/8	20	25/32	5,19	11,44	3,48	16,49	36,35	295/80R22.5	M	3,180	10,432
10.5	260	10 2/8	20	25/32	5,19	11,44	3,49	17,12	37,74	315/80R22.5	E	3,300	10,826
11	270	10 5/8	20	25/32	5,39	11,88	3,62	17,15	37,81	295/80R22.5	M	3,180	10,432
11	270	10 5/8	20	25/32	5,39	11,88	3,62	17,82	39,29	315/80R22.5	E	3,310	10,859

PRECURED TREADS - SILVERCAP



WWW.SILVERCAPRUBBER.COM