

SC 864

Recommended Application:

Highway

Optional Application:

Regional

Drive Axle

Medium and Long Distances



CHARACTERISTICS

Traditional tread with straight blocks, excellent tractive response and great water drainage.

TECHNICAL DATA

| N# | Width | | Tread Depth | | Weight/m/Lbs./Foot | | | Weight/unit/Lbs. | | Recommended Tire | Size | Length | |
|-----|-------|-------|-------------|-------|--------------------|-------|--------|------------------|-------|---------------------------------|------|--------|--------|
| | mm | In | mm | In | kg/m | Lbs/m | Lbs/ft | kg | Lbs | | | mm | ft |
| 8 | 205 | 8 2/8 | 17 | 22/32 | 3,53 | 7,78 | 2,37 | 11,06 | 24,38 | 9.00R20 | P | 3,140 | 10,302 |
| 8 | 205 | 8 2/8 | 17 | 22/32 | 3,53 | 7,78 | 2,37 | 11,34 | 25,00 | 10.00R20 | M | 3,220 | 10,564 |
| 8 | 205 | 8 2/8 | 17 | 22/32 | 3,53 | 7,78 | 2,37 | 11,61 | 25,60 | 10.00R20 | E | 3,290 | 10,794 |
| 8 | 210 | 8 2/8 | 17 | 22/32 | 3,62 | 7,98 | 2,43 | 11,34 | 25,00 | 9.00R20 | P | 3,140 | 10,302 |
| 8 | 210 | 8 2/8 | 17 | 22/32 | 3,62 | 7,98 | 2,43 | 11,63 | 25,64 | 10.00R20 | M | 3,220 | 10,564 |
| 8 | 210 | 8 2/8 | 17 | 22/32 | 3,62 | 7,98 | 2,43 | 11,91 | 26,26 | 12R22.5 11R24.5 | E | 3,290 | 10,794 |
| 8.5 | 215 | 8 5/8 | 17 | 22/32 | 3,67 | 8,09 | 2,47 | 11,47 | 25,29 | 275/80R22.5 | P | 3,120 | 10,236 |
| 8.5 | 215 | 8 5/8 | 17 | 22/32 | 3,67 | 8,09 | 2,47 | 11,77 | 25,95 | 10.00R20 | M | 3,200 | 10,499 |
| 8.5 | 215 | 8 5/8 | 17 | 22/32 | 3,67 | 8,09 | 2,47 | 12,08 | 26,63 | 12R22.5 11R24.5 | E | 3,290 | 10,794 |
| 8.5 | 220 | 8 5/8 | 17 | 22/32 | 3,79 | 8,36 | 2,55 | 11,71 | 25,82 | 275/80R22.5 | P | 3,090 | 10,138 |
| 8.5 | 220 | 8 5/8 | 17 | 22/32 | 3,79 | 8,36 | 2,55 | 12,12 | 26,72 | 295/80R22.5 | M | 3,200 | 10,499 |
| 8.5 | 220 | 8 5/8 | 17 | 22/32 | 3,79 | 8,36 | 2,55 | 12,34 | 27,21 | 11.00R20 11R24.5 | E | 3,260 | 10,696 |
| 9 | 230 | 9 | 17 | 22/32 | 3,97 | 8,75 | 2,67 | 12,26 | 27,03 | 275/80R22.5 | P | 3,090 | 10,137 |
| 9 | 230 | 9 | 17 | 22/32 | 3,97 | 8,75 | 2,66 | 12,69 | 27,98 | 295/80R22.5 11R22.5 | M | 3,200 | 10,498 |
| 9 | 230 | 9 | 17 | 22/32 | 3,97 | 8,75 | 2,66 | 12,92 | 28,48 | 12R22.5 11R24.5 | E | 3,260 | 10,695 |
| 9.5 | 240 | 9 4/8 | 17 | 22/32 | 4,13 | 9,11 | 2,78 | 12,77 | 28,15 | 275/80R22.5 | P | 3,090 | 10,137 |
| 9.5 | 240 | 9 4/8 | 17 | 22/32 | 4,14 | 9,13 | 2,78 | 13,24 | 29,19 | 295/80R22.5 | M | 3,200 | 10,498 |
| 9.5 | 240 | 9 4/8 | 17 | 22/32 | 4,14 | 9,13 | 2,78 | 13,49 | 29,74 | 12R22.5 315/80R22.5 11R24.5 | E | 3,260 | 10,695 |
| 10 | 250 | 9 7/8 | 17 | 22/32 | 4,31 | 9,50 | 2,90 | 13,79 | 30,40 | 295/80R22.5 | M | 3,200 | 10,498 |

PRECURED TREADS - SILVERCAP



WWW.SILVERCAPRUBBER.COM

SC 864

Recommended Application:

Highway

Optional Application:

Regional

Drive Axle

Medium and Long Distances



CHARACTERISTICS

Traditional tread with strenght blocks, excellent tractive response and great water drainage.

TECHNICAL DATA

| N# | Width | | Tread Depth | | Weight/m/Lbs./Foot | | | Weight/unit/Lbs. | | Recommended Tire | Size | Lenght | |
|------|-------|--------|-------------|-------|--------------------|-------|--------|------------------|-------|------------------|------|--------|--------|
| | mm | In | mm | In | kg/m | Lbs/m | Lbs/ft | kg | Lbs | | | mm | ft |
| 10 | 250 | 9 7/8 | 17 | 22/32 | 4,31 | 9,50 | 2,90 | 14,05 | 30,97 | 315/80R22.5 | E | 3.260 | 10,695 |
| 10.5 | 260 | 10 2/8 | 17 | 22/32 | 4,48 | 9,88 | 3,01 | 14,34 | 31,61 | 295/80R22.5 | M | 3.200 | 10,498 |
| 10.5 | 260 | 10 2/8 | 17 | 22/32 | 4,48 | 9,88 | 3,01 | 14,62 | 32,23 | 315/80R22.5 | E | 3.260 | 10,695 |

PRECURED TREADS - SILVERCAP



WWW.SILVERCAPRUBBER.COM