

SC 884

Recommended Application:
Mix Application
 Optional Application:
Off the Road
 Drive Axle
 Short Distances



CHARACTERISTICS

Tread rubber patten application using in rigorous conditions of use, strong blocks offering high traction capability, suitable for off-road use.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
9	230	9	22	28/32	5,26	11,60	3,53	16,86	37,17	295/80R22.5 11R22.5	M	3,210	10,531
9	230	9	22	28/32	5,26	11,60	3,53	17,24	38,01	12R22.5 11R24.5	E	3,280	10,761
9.5	240	9 4/8	22	28/32	5,52	12,17	3,71	17,76	39,15	295/80R22.5	M	3,220	10,564
9.5	240	9 4/8	22	28/32	5,52	12,17	3,71	18,20	40,12	12R22.5 315/80R22.5 11R24.5	E	3,300	10,827
10	250	9 7/8	22	28/32	5,73	12,63	3,85	18,32	40,39	295/80R22.5	M	3,200	10,499
10	250	9 7/8	22	28/32	5,73	12,63	3,85	18,78	41,40	315/80R22.5	E	3,280	10,761