

SC 908HS

Recommended Application:

Highway

Optional Application:

Regional

Trailer Axle

Short and Medium Distances



CHARACTERISTICS

Tread for diagonal tires excellent performance, developed to avoid cracks in the grooves.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Lenght	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
6.5	180	7 1/8	9	11/32	2,03	4,48	1,37	6,15	13,56	7.00 X 16 7.50 X 16	P	3.033	9,951
6.5	180	7 1/8	9	11/32	2,03	4,48	1,37	6,30	13,89	7.00 X 16	M	3.098	10,164
6.5	180	7 1/8	9	11/32	2,03	4,48	1,37	6,95	15,32	7.00 X 16 7.50 X 16	G	3.420	11,224
7.5	200	7 7/8	9	11/32	2,24	4,94	1,51	6,90	15,21	9.00X20	P	3.077	10,095
7.5	200	7 7/8	9	11/32	2,24	4,94	1,51	7,05	15,54	9.00X20	M	3.147	10,325
7.5	200	7 7/8	9	11/32	2,24	4,94	1,51	7,70	16,98	9.00X20	G	3.427	11,243
8	210	8 2/8	9	11/32	2,36	5,20	1,59	7,20	15,87	9.00X20	P	3.053	10,016
8	210	8 2/8	9	11/32	2,36	5,20	1,59	7,40	16,31	10.00X20	M	3.125	10,253
8	210	8 2/8	9	11/32	2,36	5,20	1,59	7,75	17,09	10.00X20	G	3.271	10,732
8	210	8 2/8	9	11/32	2,36	5,20	1,59	8,05	17,75	10.00X20	E	3.416	11,207
8.5	215	8 5/8	9	11/32	2,40	5,30	1,62	7,30	16,09	10.00X22	P	3.040	9,974
8.5	215	8 5/8	9	11/32	2,40	5,30	1,62	7,50	16,53	11.00X22	M	3.114	10,217
8.5	215	8 5/8	9	11/32	2,40	5,30	1,62	7,85	17,31	11.00X22	G	3.263	10,705
8.5	215	8 5/8	9	11/32	2,40	5,30	1,62	8,20	18,08	11.00X22	E	3.411	11,191
8.5	220	8 5/8	9	11/32	2,47	5,45	1,66	7,60	16,76	10.00X22	P	3.074	10,085
8.5	220	8 5/8	9	11/32	2,47	5,45	1,66	7,80	17,20	11.00X22	M	3.149	10,331
8.5	220	8 5/8	9	11/32	2,47	5,45	1,66	8,15	17,97	11.00X22	G	3.299	10,823
8.5	220	8 5/8	9	11/32	2,47	5,45	1,66	8,55	18,85	11.00X22	E	3.449	11,316

PRECURED TREADS - SILVERCAP



WWW.SILVERCAPRUBBER.COM