

SC 960

Recommended Application:
Mix Application

Optional Application:
Off the Road

Drive Axle
Short and Medium Distances



CHARACTERISTICS

Tread for bias tires with high traction power and resistant to cuts, chip and chunk.

TECHNICAL DATA

N#	Width		Tread Depth		Weight/m/Lbs./Foot			Weight/unit/Lbs.		Recommended Tire	Size	Length	
	mm	In	mm	In	kg/m	Lbs/m	Lbs/ft	kg	Lbs			mm	ft
5	150	5 7/8	12	15/32	2.10	4.63	1.41	5.10	11.24	7.00 X 16	MICRO	2.430	7.972
5.5	160	6 2/8	12	15/32	2.26	4.98	1.52	5.44	11.99	7.00 X 16 7.50 X 16	MICRO	2.410	7.906
6.5	180	7 1/8	15	19/32	3.02	6.66	2.03	7.33	16.16	215/75R17.5	MICRO	2.430	7.972
7	190	7 4/8	15	19/32	3.19	7.03	2.14	7.90	17.42	215/75R17.5	MICRO	2.480	8.136
7	190	7 4/8	15	19/32	3.19	7.03	2.14	9.79	21.58	9.00X20	P	3.070	10.072
7	190	7 4/8	15	19/32	3.19	7.03	2.14	10.17	22.42	10.00X20	M	3.190	10.465
7.5	200	7 7/8	15	19/32	3.39	7.47	2.28	10.70	23.59	10.00X20	M	3.160	10.367
8	210	8 2/8	15	19/32	3.54	7.80	2.37	11.20	24.69	10.00X20	M	3.170	10.4

PRECURED TREADS - SILVERCAP



WWW.SILVERCAPRUBBER.COM